



Ovale zuignap
met nippel

Oval suction cup
with thread nipple
male thread

326

Silicone (SI) Silicone (SI)	Nitrile (NBR) Nitrile (NBR)	Hoge temp (HT) Hight temp (HT)	Nippel Fitting	Afmetingen Dimensions				
Artikel - Nr. Article - No.	Artikel - Nr. Article - No.	Artikel - Nr. Article - No.	Type Type	A	B	G	H 1	Slag Stroke
326 03 507	327 03 507	328 03 507	N 003	3,5	7	M 5	8	0,8
326 05 515	327 05 515	328 05 515	N 021	5	15	M 5	17	0,7
326 06 518	327 06 518	328 06 518	N 021	6	18	M 5	17	0,8
326 08 824	327 08 824	328 08 824	N 022	8	24	1/8	17	1
326 10 830	327 10 830	328 10 830	N 022	10	30	1/8	17	1,5
326 15 445	327 15 445	328 15 445	N 023	15	45	1/4	26	2
326 20 460	327 20 460	328 20 460	N 023	20	60	1/4	26	2,5
326 25 475	327 25 475	328 25 475	N 023	25	75	1/4	26	2,8

320

Toepassing

- De materiaaleigenschappen vindt u op de informatiepagina (pagina 36 - 37).
- Schroefdraadnippels met inwendige schroefdraad op aanvraag.

Application

- You will find information about the corresponding material properties on the fact sheet (page 36 - 37).
- Thread nipple with female thread on request.