



Polyurethaan (PU) Polyurethane (PU)	Silicone (SI) Silicone (SI)	Nitrile (NBR) Nitrile (NBR)	Hoge temp (HT) Hight temp (HT)	Nippel Fitting	Afmetingen Dimensions			
Artikel - Nr. Article - No.	Artikel - Nr. Article - No.	Artikel - Nr. Article - No.	Artikel - Nr. Article - No.	Type Type	A	d	H 2	Slag Stroke
331 15 010	332 15 010	333 15 010	334 15 010	N 004	10	4	13,5	4
331 15 015	332 15 015	333 15 015	334 15 015	N 004	15	4	16	6
331 15 020	332 15 020	333 15 020	334 15 020	N 007	20	6	22	9
-	332 15 025	333 15 025	334 15 025	N 016	25	NN	NN	NN
331 15 030	332 15 030	333 15 030	334 15 030	N 007	30	6	30,5	13
331 15 040	332 15 040	333 15 040	334 15 040	N 007	40	6	30,5	13
331 15 050	332 15 050	333 15 050	334 15 050	N 008	50	8	36,5	20
-	332 15 060	333 15 060	334 15 060	N 008	60	NN	NN	NN
331 15 075	332 15 075	333 15 0754	-	N 009	75	M5x1,25	43,5	22

330

**Toepassing**

**Application**

- De materiaaleigenschappen vindt u op de informatiepagina (pagina 36 - 37).
- You will find information about the corresponding material properties on the fact sheet (page 36 - 37).